

[CGFR 65-50, 30 FR 16953, Dec. 30, 1965, as amended by CGFR 67-87, 32 FR 19181, Dec. 20, 1967; CGD 86-036, 57 FR 48325, Oct. 23, 1992; CGD 95-028, 62 FR 51204, Sept. 30, 1997]

#### **§ 77.35-15 Stowage.**

(a) The fireman's outfit, together with such other items of equipment as the master may deem necessary, shall be stowed in convenient, accessible locations for use in case of emergency. One outfit shall be stowed in or near the pilothouse. Where additional outfits are required by table 77.35-10(b), one of the additional outfits shall be stowed preferably adjacent to the main entrance to the machinery space. Other additional outfits shall be stowed in convenient accessible locations remote from the pilothouse.

(b) [Reserved]

#### **§ 77.35-20 Spare charges.**

(a) A complete recharge shall be carried for each self-contained breathing apparatus, and a complete set of spare batteries shall be carried for each flashlight. The spares shall be stowed in the same location as the equipment it is to reactivate.

(b) [Reserved]

#### **§ 77.35-90 Vessels contracted for before November 23, 1992.**

Vessels contracted for before November 23, 1992, must meet the following requirements:

(a) Each vessel must satisfy §§ 77.35-5 through 77.35-20 concerning the number of items and the method of stowage of equipment.

(b) Items of equipment previously approved, but not meeting the applicable specifications set forth in § 77.35-5, may continue in service as long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection; but each item in an installation or a replacement must meet all applicable specifications.

(c) After November 23, 1994, each respirator must either satisfy § 77.35-5(b) or be a self-contained compressed-air breathing apparatus previously approved by MSHA and NIOSH under part 160, subpart 160.011, of this chapter.

[CGD 86-036, 57 FR 48325, Oct. 23, 1992]

### **Subpart 77.40—Pilot Boarding Equipment**

#### **§ 77.40-1 Pilot boarding equipment.**

(a) This section applies to each vessel that normally embarks or disembarks a pilot from a pilot boat or other vessel.

(b) Each vessel must have suitable pilot boarding equipment available for use on each side of the vessel. If a vessel has only one set of equipment, the equipment must be capable of being easily transferred to and rigged for use on either side of the vessel.

(c) Pilot boarding equipment must be capable of resting firmly against the vessel's side and be secured so that it is clear from overboard discharges.

(d) Each vessel must have lighting positioned to provide adequate illumination for the pilot boarding equipment and each point of access.

(e) Each vessel must have a point of access that has—

(1) A gateway in the rails or bulwark with adequate handholds; or

(2) Two handhold stanchions and a bulwark ladder that is securely attached to the bulwark rail and deck.

(f) The pilot boarding equipment required by paragraph (b) of this section must include at least one pilot ladder approved under subpart 163.003 of this chapter. Each pilot ladder must be of a single length and capable of extending from the point of access to the water's edge during each condition of loading and trim, with an adverse list of 15°.

(g) Whenever the distance from the water's edge to the point of access is more than 30 feet, access from a pilot ladder to the vessel must be by way of an accommodation ladder or equally safe and convenient means.

(h) Pilot hoists, if used, must be approved under subpart 163.002 of this chapter.

[CGD 79-032, 49 FR 25455, June 21, 1984]

## **PART 78—OPERATIONS**

### **Subpart 78.01—Application**

Sec.

78.01-1 General.

78.01-2 Incorporation by reference.

**Pt. 78**

**Subpart 78.05—Notice to Mariners and Aids to Navigation**

- 78.05-1 Duty of officers.
- 78.05-5 Charts and nautical publications.

**Subpart 78.07—Notice and Reporting of Casualty and Voyage Records**

- 78.07-1 Notice and reporting of casualty and voyage records.

**Subpart 78.10—Persons Allowed in Pilothouse and on Navigation Bridge**

- 78.10-1 Persons excluded.

**Subpart 78.12—Stability Information**

- 78.12-1 Posting of stability letter.

**Subpart 78.13—Station Bills**

- 78.13-1 Muster lists, emergency signals, and manning.

**Subpart 78.15—Doors Closed at Sea**

- 78.15-1 Subdivision bulkheads.

**Subpart 78.16—Port Lights**

- 78.16-1 General.

**Subpart 78.17—Tests, Drills, and Inspections**

- 78.17-1 Application.
- 78.17-3 Watertight doors.
- 78.17-5 Valves and closing appliances.
- 78.17-10 Loudspeaker system.
- 78.17-15 Steering gear, whistle, and means of communication.
- 78.17-20 Drafts and load line markings.
- 78.17-22 Verification of vessel compliance with applicable stability requirements.
- 78.17-25 Sanitation.
- 78.17-30 Examination of boilers and machinery.
- 78.17-33 Loading doors.
- 78.17-35 Hatches and other openings.
- 78.17-45 Emergency lighting and power systems.
- 78.17-50 Emergency training, musters, and drills.
- 78.17-65 Smoke detecting system.
- 78.17-75 Requirements for fuel oil.
- 78.17-80 Firefighting equipment, general.

**Subpart 78.19—Auto Pilot**

- 78.19-1 Use of auto pilot.

**Subpart 78.21—Maneuvering Characteristics**

- 78.21-1 Data required.

**46 CFR Ch. I (10-1-08 Edition)**

**Subpart 78.23—Whistling**

- 78.23-1 Unnecessary whistling prohibited.

**Subpart 78.27—Searchlights**

- 78.27-1 Improper use prohibited.

**Subpart 78.30—Lookouts, Pilothouse Watch, Patrolmen, and Watchmen**

- 78.30-5 Pilothouse watch.
- 78.30-10 Supervised patrol.
- 78.30-15 Watchmen.
- 78.30-20 Master's and officer's responsibility.

**Subpart 78.33—Reports of Accidents, Repairs, and Unsafe Equipment**

- 78.33-1 Repairs of boiler and pressure vessels.
- 78.33-5 Accidents to machinery.
- 78.33-10 Notice required before repairs.

**Subpart 78.35—Communication Between Deckhouses**

- 78.35-1 When required.

**Subpart 78.36—Work Vests**

- 78.36-1 Application.
- 78.36-5 Approved types of work vests.
- 78.36-10 Use.
- 78.36-15 Shipboard stowage.
- 78.36-20 Shipboard inspections.
- 78.36-25 Additional requirements for hybrid work vests.

**Subpart 78.37—Logbook Entries**

- 78.37-1 Application.
- 78.37-3 Logbooks and records.
- 78.37-5 Actions required to be logged.
- 78.37-10 Official log entries.

**Subpart 78.40—Vehicular Ferries**

- 78.40-1 Stowage of vehicles.
- 78.40-5 Securing of vehicles.
- 78.40-10 No smoking permitted.

**Subpart 78.45—Display of Plans**

- 78.45-1 When required.

**Subpart 78.47—Markings for Fire and Emergency Equipment, Etc.**

- 78.47-1 Application.
- 78.47-3 General.
- 78.47-5 General alarm contact makers.
- 78.47-7 General alarm bells.
- 78.47-9 Carbon dioxide alarm.
- 78.47-10 Manual alarm boxes.
- 78.47-13 Fire detecting and manual alarm, automatic sprinkler, and smoke detecting alarm bells.

## Coast Guard, DHS

## § 78.01-2

- 78.47-15 Fire extinguishing system branch lines.
- 78.47-17 Fire extinguishing system controls.
- 78.47-20 Fire hose stations.
- 78.47-23 Supervised patrol stations.
- 78.47-25 Emergency squad equipment.
- 78.47-27 Self-contained breathing apparatus.
- 78.47-30 Hand portable fire extinguishers.
- 78.47-33 Emergency lights.
- 78.47-35 Fire doors.
- 78.47-37 Watertight doors.
- 78.47-38 Valves and closing appliances.
- 78.47-40 Exit signs.
- 78.47-45 Markings for lifesaving appliances, instructions to passengers, and stowage locations.
- 78.47-53 Automatic ventilation dampers.
- 78.47-55 Instructions for changing steering gear.
- 78.47-57 Rudder orders.
- 78.47-70 Portable magazine chests.
- 78.47-75 Ventilation alarm failure.
- 78.47-90 Vessels contracted for prior to November 19, 1952.

### Subpart 78.50—Markings on Vessels

- 78.50-1 Application.
- 78.50-5 Hull markings.
- 78.50-10 Draft marks and draft indicating systems.
- 78.50-15 Load line marks.

### Subpart 78.55—Carrying of Excess Steam

- 78.55-1 Master and chief engineer responsible.

### Subpart 78.57—Routing Instructions

- 78.57-1 All personnel must comply.

### Subpart 78.60—Compliance With Provisions of Certificate of Inspection

- 78.60-1 Master or person in charge responsible.

### Subpart 78.65—Exhibition of License

- 78.65-1 Licensed officers.

### Subpart 78.70—De-Energizing of Cargo Hold Lighting Circuits When Grain or Other Combustible Bulk Cargo Is Carried

- 78.70-1 Master's responsibility.
- 78.70-5 Warning notice posted.

### Subpart 78.83—Operation of Vehicles in Enclosed Locations

- 78.83-1 Special operating conditions.

### Subpart 78.90—Pilot Boarding Operations

- 78.90-1 Pilot boarding operation.

### Subpart 78.95—Person in Charge of Transfer of Liquid Cargo in Bulk

- 78.95-1 General.

AUTHORITY: 33 U.S.C. 1321(j); 46 U.S.C. 2103, 3306, 6101; 49 U.S.C. 5103, 5106; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; E.O. 12777, 56 FR 54757, 3 CFR, 1991 Comp., p. 351; Department of Homeland Security Delegation No. 0170.1.

SOURCE: CGFR 65-50, 30 FR 16955, Dec. 30, 1965, unless otherwise noted.

### Subpart 78.01—Application

#### § 78.01-1 General.

(a) The provisions of this part shall apply to all vessels except as specifically noted.

(b) [Reserved]

#### § 78.01-2 Incorporation by reference.

(a) Certain material is incorporated by reference into this part with the approval of the Director of the Federal Register under 5 U.S.C. 552(a) and 1 CFR part 51. To enforce any edition other than that specified in paragraph (b) of this section, the Coast Guard must publish notice of change in the FEDERAL REGISTER; and the material must be available to the public. All approved material is available for inspection or at the National Archives and Records Administration (NARA), and at the U.S. Coast Guard, Lifesaving and Fire Safety Division (G-MSE-4), 2100 Second Street SW., Washington, DC 20593-0001, and is available from the sources indicated in paragraph (b) of this section. For information on the availability of this material at NARA, call 202-741-6030, or go to: [http://www.archives.gov/federal\\_register/code\\_of\\_federal\\_regulations/ibr\\_locations.html](http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html).

(b) The material approved for incorporation by reference in this part and the sections affected are as follows:

*American Society for Testing and Materials (ASTM)*

100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

ASTM D 93-97, Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester—78.17-75